



CD-P750DAB CD Player/DAB+/FM

251831

SRP CHF 599.00

The CD-P750DAB is a slot-load CD Player with FM/DAB+ tuner supporting playback from CDs, USB memory devices, SD cards and Bluetooth

PRODUCT DETAILS

Slot-load CD drive mechanism

The CD-P750DAB employs a slot-load CD drive mechanism that is designed for professional audio applications. The CD drive mechanism enables users of quick loading.

Can play files from CDs, USB memory devices and SD cards

The CD-P750DAB supports playback from various media such as audio CD, data CD, SD card and USB memory devices, and the file formats it supports are WAV, MP3, AAC and WMA.

Wireless playback from Bluetooth® devices

Audio files can be played from Bluetooth® devices such as smartphones, tablets and portable music players. In addition to the general codec, SBC, the high-quality sound codecs such as AAC and Qualcomm®aptX™ HD are supported. This enables easy playback of audio files without fussing with cables or file formats.

Employs DAB+/FM tuner

The CD-P750DAB employs a DAB+/FM tuner. 20 each of DAB+ and FM station presets can be set. An independent tuner output connector is incorporated, enabling simultaneous playback with other media.

Employs an external input connector

The CD-P750DAB employs a stereo mini AUX IN connector. This enables the CD-P750DAB to play audio from portable music players without Bluetooth®.

Enables dubbing of audio from a CD or tuner to a USB memory device or SD card

Audio from an audio CD or tuner can be dubbed to an SD/SDHC card or USB memory device using only the CD-P750DAB – no need for a computer. Just press the dubbing button and play the audio to start dubbing.

What's in the box

- AC power cord
- Remote control (RC-1336)
- FM antenna
- Owner's manual

Specs

Product Attributes

EAN:	4907034223909
Manufacturer number:	CD-P750DAB-B
Product weight:	4.5 kilograms

Audio Codecs & Formats

CD formats:	CD CD-R CD-RW
Supported file formats:	MP3 WMA WAV AAC SBC AAC aptX HD aptX
Bluetooth codecs:	5.1
Bluetooth version:	

Energy Management

Power consumption:	20
--------------------	----

Audio Outputs

6.3mm jack:	1
Power & impedance 6.3mm jack:	20mW + 20mW (THD+N 0.1% or less, into 32 load)
Coaxial:	1
Optical/Toslink:	1
RCA:	2
Output level & impedance RCA:	-10dBV (0.316Vrms) to +6dBV (2.0Vrms). 200.
USB 2.0:	0

Dimensions and Weight

Product height:	5.88
Product width:	48.26
Product length:	29.71
Product weight:	3.6
Packsize height:	29
Packsize width:	50
Packsize length:	64.5
Packaged weight:	16

Control Methods

Controls:

On Device
Remote Control