



## VRDS-701T Transportador de CD con mecanismo VRDS, negro

252429

SRP 1 999,00 €

The VRDS-701T CD transport utilizes our newly-developed VRDS mechanism. The VRDS is a TEAC-original CD drive mechanism that reduces rotation vibration and other unwanted vibration by clamping the CD to an aluminum turntable with the same diameter in order to maximize inertial mass. When used in combination with a UD-701N playback is possible using the discrete DAC in the UD-701N as well as with MQA full decoding. Of course, you can also use it together with a DAC of your choosing, and build a system as you like. The inclusion of a 10MHz clock input enables flexible integration with systems that are synchronized using an external clock.

Color



### DETALLES DEL PRODUCTO

#### Newly-developed VRDS mechanism

Starting with a drive we developed that has a long record of use in broadcast applications, we added VRDS technologies, which are part of our TEAC legacy.

#### Vibration-Free Rigid Disc-Clamping System (VRDS)

This TEAC-original CD drive mechanism reduces rotation vibration of the disc itself as well as unwanted mechanism vibration by clamping the CD to an aluminum turntable with the same diameter and maximizing inertial mass in order to stabilize rotation. Servo current is reduced with the turntable by correcting disc warping and distortion and improving the relative optical axis precision of the pickup and disc pit side. This realizes reduced disc reading errors and outstanding audio quality.

#### Bridge section supports the VRDS

For the bridge that supports the turntable, we carefully selected lightweight materials that are very rigid and do not transmit vibration. By naturally settling vibrations quickly, we have realized a wide, dynamic sound. The bridge, which has a torus structure made of resin, is only fixed on one side, and propagation of vibration from the CD mechanism to the opposite side through the bridge is suppressed, so the entire mechanism minimizes unwanted sympathetic vibrations.

#### Semi-floating mounting

The entire CD mechanism is mounted on the sub-chassis in a semi-floating state. By controlling the transmission of vibrations between the CD mechanism and the chassis, the impact of sympathetic

vibrations is abated, and natural playback sound is realized throughout the frequency range. By isolating motor vibrations from the main chassis, sympathetic vibrations within the chassis are prevented. At the same time, the CD mechanism is also isolated from external vibrations. Reading precision is also increased by isolating the CD mechanism from external vibrations.

**Enhanced digital output**

By eliminating the DAC function, the internal circuitry has been optimized for digital output. We have pursued higher audio quality by, for example, using larger components that did not fit in more limited space.

**MQA CDs can be played back using the built-in MQA core decoder**

The VRDS-701T has a built-in MQA core decoder and can digitally output MQA CDs at 88.2 kHz . Moreover, when used together with a DAC that has an MQA rendering function, playback using MQA full decoding is also possible.

**10MHz external clock input**

The 10MHz clock input allows synchronization with an external clock. In addition to improving audio quality during playback with the VRDS-701T, this also enables synchronization of the entire system with a clock generator.

**Power supply enhanced using 2 high-capacity toroidal core transformers**

Independent high-capacity toroidal core transformers are dedicated to the digital control section and the CD mechanism. These 2 high-capacity toroidal core transformers enable current to be supplied with greater stability.

**Thorough design for vibration control**

Power transformers, which tend to generate vibration, are mounted on a floating structure, separating and isolating them from the bottom panel. The side fins for heat dissipation have been tailored so that each one has a different length in order to eliminate sympathetic vibrations.

**Three supporting pinpoint feet made of machined steel with a unique structure**

The circuit board attachment screws have been kept to a minimum. Furthermore, steel pinpoint feet that use an original TEAC design with a new structure to provide a suitable amount of play in the connection between them and the bottom panel, are employed to thoroughly control vibrations that could affect audio quality.

**Control connectors enable coordinated use with other devices**

RS-232C is present for integration with popular control systems, and trigger input and output connectors enable power coordination with other devices.

**Included accessories**

- AC cord
- Remote control (RC-1338)
- AAA batteries × 2
- Foot pads × 3
- Owner's manual

**Especificaciones**

**Product Attributes**

EAN:	4907034224425
Manufacturer number:	VRDS-701T-B
Product weight:	5.0 kilograms

**Codecs y formatos de audio**

Formatos de CD:	CD
	CD-R
	CD-RW
	MQA-CD

**Gestión de la energía**

Consumo de energía: 0.4-40

**Salidas de audio**

Coaxial: 1

Nivel de salida & impedancia coaxial: 0.5Vp-p 75

Óptico: 1

**Dimensiones y peso**

Altura del producto: 11.1

Ancho del producto: 44.4

Longitud del producto: 33.3

Peso del producto: 10.1

Altura del paquete: 29.7

Anchura del paquete: 64.4

Longitud del paquete: 49.5

Peso total del paquete: 13.8

**Métodos de control**

Controles: En el dispositivo  
Control remoto  
RS-232